


Product	Sinopec 75W/90 GL-5 Fully Synthetic Heavy Duty Vehicle Gear Oil
Summary	<p>Product description</p> <p>Sinopec 75W/90 GL-5 Fully Synthetic Heavy Duty Vehicle Gear Oil is formulated with polyalphaolefin (PAO) base oil and selected multifunctional additives. The high viscosity index, excellent oxidation resistance and high load-carrying capacity meet the lubrication requirements of hypoid gears in a variety of vehicles, providing an extended oil drain interval and ensuring excellent load-carrying ability even under shock-loading conditions. The product's performance exceeds that of a conventional mineral-oil based GL-5 quality Vehicle Gear Oil.</p>

Available sizes



PAIL – 18L



DRUM – 200L



IBC – 1000L

Also
available
in bulk

Applications

Sinopec 75W/90 GL-5 Fully Synthetic Heavy Duty Vehicle Gear Oil is suitable for use in:

- Drive axles (front or rear) of heavy duty vehicles.
- Some transmission gears, especially hypoid gears, in heavy duty vehicles.
- Axles and transmission systems that require a GL-5 quality oil.

Features and benefits

- The very high viscosity index, provided by the fully synthetic formulation, ensures excellent low- and high-temperature performance, and reduces gear wear at low-temperature start up.
- Advanced sulfur-phosphorus extreme pressure (EP) additive technology provides outstanding load-carrying capacity, and protects axles and gears operating under severe service conditions (e.g. low speed, high torque and high speed, high load).
- Excellent thermal and oxidation stability protect against the formation of deposits and sludge, prolong oil service life and extend oil drain intervals.
- The low coefficient of friction and high lubricity, provided by the PAO base oil, reduce resistance at start up and during operation, lowering power consumption and operating costs.
- Good oil film thickness protects against gear wear, scoring and pitting, and also prevents corrosion or spalling of gear surfaces.
- Good antifoaming properties ensure a good oil film is maintained during service, and avoid oil overflow and leakage.
- Fully compatible with the seal and gasket materials used in most conventional vehicles.
- Good resistance against rust and corrosion extends component life.
- The 75W-90 multigrade can be used year round, without the need for seasonal change, and so can reduce oil inventory costs.

Product Data Sheet

Typical data

Sinopec 75W/90 GL-5 Fully Synthetic Heavy Duty Vehicle Gear Oil	
SAE grade	75W-90
Kinematic viscosity, ASTM D 445	
cSt @ 40°C	79.3
cSt @ 100°C	16.5
Viscosity, Brookfield, ASTM D 2983	
cP @ -40°C	47,000
Viscosity index, ASTM D 2270	225
Copper corrosion, 3 hours @ 121°C, ASTM D 130	1b
Pour point, °C, ASTM D 97	-42
Flash point (COC), °C, ASTM D 92	215
Density @ 20°C, kg/l, ASTM D 4052	0.8787
Colour	yellow

These data are given as an indication of typical values and not as exact specifications.

Industry and OEM specifications

Sinopec 75W/90 GL-5 Fully Synthetic Heavy Duty Vehicle Gear Oil meets the performance requirements of the following industry specifications:	
API	GL-5
API	MT-1
MIL	MIL-PRF-2105E
SAE	J2360

Product Data Sheet

Sinopec 75W/90 GL-5 Fully Synthetic Heavy Duty Vehicle Gear Oil meets the performance requirements of the following OEM specifications:	
Arvin Meritor+	0-76-A/B/D
DAF+	API GL-5 or J2360
Iveco+	API GL-5 or J2360
Mack	GO-J
MAN	342 M-2
Renault+	API GL-5 or J2360
Scania+	STO 1:0
Volvo+	API GL-5
ZF	TE-ML 05A – axles for off-road vehicles
ZF	TE-ML 07A – hydrostatic drives
ZF	TE-ML 08 – steering systems
ZF	TE-ML 12E – axles for buses
ZF	TE-ML 16 B,C,D – transmissions for rail vehicles
ZF	TE-ML 17B – transmissions and axles for lift trucks
ZF	TE-ML 19B – transfer and offset transmissions

+Self-certifying, meets requirements and is recommended for service fill use (formal approvals for use are not available). The vehicle service manual should also be reviewed to gearbox type and any special requirements

Accuracy of information

Data provided in this PDS is typical and subject to change as a result of continuing product research and development. The information given was correct at the time of printing. The typical values given are subject to variations in the testing procedures and the manufacturing process may also result in slight variations. Sinopec guarantees that its lubricants meet any industry and OEM specifications referred to on this data sheet.

Sinopec cannot be held responsible for any deterioration in the product due to incorrect storage or handling. Information on best practice is available from your local distributor.

Product and environmental safety

This product should not cause any health problems when used in the applications suggested and when the guidance provided in the Material Safety Data Sheet (MSDS) is followed. Please consult the MSDS for more detailed advice on handling; MSDSs are available from your local distributor. Do not use the product in applications other than those suggested.

As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

The SINOPEC trademark is registered and protected.

Issued: March 2017

© Sinopec 2017

Sinopec 75W/90 GL-5 Fully Synthetic Heavy-duty Vehicle Gear Oil

SINOPEC

Premium Lubricants



PT. MASA JAYA PERKASA

M info@masajayaperkasa.com

**Jl. Hayam Wuruk No. 76,
Jakarta Barat, DKI Jakarta 11160**

(+62)21-649-6496

(+62)852-1116-7713