

Product

Sinopec M0583A Stainless Steel Drawing Oil

Summary

Product description

Sinopec M0583A Stainless Steel Drawing Oil is manufactured from a highly refined mineral oil, and various functional additives, with good lubricating perpormance, It is suitable for lubricating in the stainless steel wire drawing, etc.

Available sizes



Also available in bulk

Applications

Sinopec M0583A Stainless Steel Drawing Oil is suitable for use in:

The stainless steel wire drawing for lubricating.

Features and benefits

- Outstanding extreme pressure and lubrication performances.
- Outstanding extreme pressure performance resulting in extended mould life.



Typical data

Sinopec M0583A Stainless Steel Drawing Oil	
Appearance	Transparent liquid
Kinematic viscosity (40°C), mm²/s	207.2
Flash point(COC), ℃	216
Corrosion Test (45# steel, 100°C, 3h)	Pass
Max Nonseizure Load(PB), N	1026
Weld Point (PD), N	7845

These data are given as an indication of typical values and not as exact specifications.

Industry and OEM specifications

Sinopec M0583A Stainless Steel Drawing Oil meets the performance requirements of the following specification:	
SINOPEC	SHRHYXY15213-2012

Notices

Avoid to be mixed with water or impurities.

Packaging \storage and transportation

- 200L iron drum.
- Product logo packaging, transportation, storage, delivery and acceptance complies with SH/T 0164.

Accuracy of information

Data provided in this PDS is typical and subject to change as a result of continuing product research and development. The information given was correct at the time of printing. The typical values given are subject to variations in the testing procedures and the manufacturing process may also result in slight variations. Sinopec guarantees that its lubricants meet any industry and OEM specifications referred to on this data sheet.

Sinopec cannot be held responsible for any deterioration in the product due to incorrect storage or handling. Information on best practice is available from your local distributor.

Product and environmental safety

This product should not cause any health problems when used in the applications suggested and when the guidance provided in the Material Safety Data Sheet (MSDS) is followed. Please consult the MSDS for more detailed advice on handling; MSDSs are available from your local distributor. Do not use the product in applications other than those suggested.

As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

The SINOPEC trademark is registered and protected.

Issued: March 2017 © Sinopec 2017

Sinopec M0583A Stainless Steel Drawing Oil



SINOPEC Premium Lubricants





PT. MASA JAYA PERKASA



info@masajayaperkasa.com



Jl. Hayam Wuruk No. 76, Jakarta Barat, DKI Jakarta 11160



(+62)21-649-6496



(+62)852-1116-7713